HT-360AET

Active ETH Gateway AX10500 Tri-Band WiFi6E





Product Specifications



Wireless Features.

Wireless Standard	80
Wireless Signal Rates	Up
2.4GHz Band	3x3
5GHz Band	4x
6GHz Band	4x
Operating Mode	Au
Wireless Communication	En
Wireless Security	WF
Auto channel selection	Su
Single SSID	Su
Steering	Ba
Security	En
SSID Broadcast Control	En
Transmission speed	Wi

802.11 a/b/g/n/ac/ax
Up to 10.5 Gbps
3x3 11ax up to 900 Mbps
4x4 11ax up to 4.8 Gbps
4x4 11ax up to 4.8 Gbps
Auto by default
Enable
WPA / WPA2 / WPA3
Supported
Supported
Band & Client steering
Enabled
Enabled
Wireless Auto

2.5Gbps link speed

WAN connectivity on DHCP by default

Supported Supported

Supported

Supported

Supported Supported

Supported

Supported

Supported



Network Features.

Active ETH

PPPoE, DHCP, static IP connectivity
NAT
MultiRangePort Forwarding Virtual server, special Application & DMZ host
DHCP Server
UPnP, DDNS
MAC Address Cloning
IGMP Snoop
QoS Traffic Control (IP)
DNS Relay
Café-style guest network



Smart Led.

Red	Boot or network fail
Blue	ready to install
White	Internet access
Green	Internet access without WiFi connectivity



NAT for basic firewall support	Supported
Packet filtering firewall	Supported
Password authentication to gateway	Supported



System Features.

Configuration download / upload	Supported
Telnet / SSH	Supported
SNTP	Supported
Remote & Web management	Supported
Self-Healing	Supported
TR-069 / TR-181	Supported
Echo mode (wireless switch schedule)	Supported



Physical Features.

Interface	WAN, FXS, Ethernet, Power, USB3.1
Power Supply	12V 2.5A DC
Button	Reset, Power On/Off, WPS, WiFI On/Off
Dimension	200mm x 50mm x 255mm
Operating Temperature	0° C ~ 40° C
Operating Humidity	10% ~ 90%, noncondensing
Storage Temperature	-20° C ~ 70° C
Storage Humidity	5% ~ 90%, noncondensing

Interface.



